

High Pressure Cleaner

KS823

Hot water resistant





**1400
U/min**

TSS







INOX



Type	KS823	KS823-INOX
Voltage	1/N/PE/AC/50Hz/230V	
Operating pressure	30-120bar/3-12MPa	
Max. pressure	140bar/14MPa	
Discharge capacity	300-720l/h	
Nozzle size	050	
Max. Inlet temperature	80°C	
Pump speed	1400rpm	
Connected load	2,6kW/12,5A	
Electrical protection	16A slow	
Weight net/with package	110kg/125kg	110kg/125kg
Dimensions device/with package (LxWxH)	102x50x50cm/119x88x127cm	102x50x50cm/119x88x127cm
	<ul style="list-style-type: none"> • 10m HP-Hose DN08 - 315bar • Trigger-Gun with swivel • Spray-Lance 900mm c/w Nozzle-Protection • Stainless-Steel Jet-Nozzle 25° • 4l Water-Storage tank • Water-Supply separation acc. DIN EN 1717 class 4 • Chemical supply in high-pressure Jet c/w Metering-valve 	<ul style="list-style-type: none"> • Stainless Steel (Food-Safe) • 10m HP-Hose DN08 - 315bar • Trigger-Gun with swivel • Spray-Lance 900mm c/w Nozzle-Protection • Stainless-Steel Jet-Nozzle 25° • 4l Water-Storage tank • Water-Supply separation acc. DIN EN 1717 class 4 • Chemical supply in high-pressure Jet c/w Metering-valve

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless- steel), wall-bracket, opening of the device hood by supporting gas pressure springs, triplex-piston pump with brass pump head, hot-water resistant up to 80°C, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min with leakage-recognition, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, robust rotary on-off switch, 7,5m connection cable.

Art.No.	157	157000
---------	-----	--------