

# High Pressure Cleaner

## KD1140-F

Food progressing  
with stainless steel pump, hot water resistant





**1400  
U/min**

**TSS**

**TOTAL  
STOP**











INOX

Type		KD1140-F-Standard	KD1140-F-Premium
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> <li>10m HP-Hose DN08 - 315bar blue</li> </ul>	<ul style="list-style-type: none"> <li>Hose-Reel</li> </ul>
Operating pressure	30-180bar/3-18MPa	<ul style="list-style-type: none"> <li>Trigger-Gun with swivel</li> </ul>	<ul style="list-style-type: none"> <li>15m HP-Hose DN08 - 315bar blue</li> </ul>
Max. pressure	200bar/20MPa	<ul style="list-style-type: none"> <li>Double Spray-Lance 900mm c/w Nozzle-Protection</li> </ul>	<ul style="list-style-type: none"> <li>Trigger-Gun with swivel</li> </ul>
Discharge capacity	300-1000l/h	<ul style="list-style-type: none"> <li>Stainless-Steel Jet-Nozzle 25°</li> </ul>	<ul style="list-style-type: none"> <li>Double Spray-Lance 900mm c/w Nozzle-Protection</li> </ul>
Nozzle size	055	<ul style="list-style-type: none"> <li>25l Cleaning-Detergent tank</li> </ul>	<ul style="list-style-type: none"> <li>Stainless-Steel Jet-Nozzle 25°</li> </ul>
Max. Inlet temperature	80°C	<ul style="list-style-type: none"> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> </ul>
Pump speed	1400rpm		<ul style="list-style-type: none"> <li>17l Water-Storage tank</li> </ul>
Connected load	6,9kW/10,3A		<ul style="list-style-type: none"> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> </ul>
Electrical protection	3x16A slow		<ul style="list-style-type: none"> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		98x62x100cm/109x63x112cm	98x62x100cm/109x63x112cm

Food progressing with abrasion resistant high pressure hose blue, self-supporting, robust, corrossions free, rotation-moulded device-chassis for food industry, stainless steel, impact-resistant device-cover made of ABS, triplex-piston pump with chrome, nickel plated pump head (hot water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar stainless steel.

<b>Art.No.</b>	551003	551004
----------------	--------	--------